

Stromschienenstrahler aus Aludruckguss mit HV-LED Oberfläche in weiß, schwarz, silber matt oder chrom Satinierter bündiger Diffusor aus PMMA Leuchtenkopf 350° drehbar und 90° schwenkbar

Mains voltage LED track die cast aluminium spotlight White, black, silver matt or chrome finish Glossy flush mount PMMA diffuser Spotlight head 350° swiveling and 90° tilting

Proiettore a LED a tensione di rete per binario trifase Finitura in bianco, nero, grigio opaco o cromo Diffusore satinato rasato in PMMA Testa proiettore girevole a 350° e inclinabile a 90°

Projecteur en LED à tension de réseau pour rail triphase Fini en blanc, noir, gris mat ou chrome Diffuseur satiné ramassé en PMMA Tête projecteur tournant à 350° et pivotant à 90°

- W2** = LED 2700K
- W3** = LED 3000K
- W4** = LED 4000K

3-Phasen Schienensystem: Seite 450 - 455
3-phase track system: page 450 - 455




IP 20

LITIN AC TRACK

220-240V AC · CRI>80 · Binning SDCM 3

SYS 10W

651-001021413XX	W2	600lm
651-001021419XX	W3	600lm
651-001021414XX	W4	600lm



ENTBLENDUNGSRING / NO GLARE DIFFUSER

gerade, mit Bajonettverschluss
straight, with bayonet cap

- 651-000014**
- 651-000015**
- 651-000016**



ENTBLENDUNGSRING / NO GLARE DIFFUSER

schräg, mit Bajonettverschluss
angular with bayonet cap

- 651-000024**
- 651-000025**
- 651-000026**



ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

XX = FARBE / COLOUR

- SM** silver matt = 44
- W** white = 55
- S** black = 66

444 LITIN AC TRACK

Design: INHOUSE