



LED Hängeleuchte aus stranggepresstem Aluminiumprofil
Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet
Abdeckung mit Mikropriemnoptik oder Opaldiffusor
Inkl. 3000mm werkzeuglos höhenverstellbarer Abhängung

LED pendant profile made of extruded aluminium
Anodised surface, black or white powder coated
Opal or microprismatic diffuser
Included 3m suspension cable, adjustable without tools

Sospensione a LED in alluminio estruso
Anodizzato o verniciato a polveri in bianco o nero
Diffusore opale o microprismatico
Compreso di cavo da 3m, regolabile senza attrezzi

Suspension à LED en aluminium extrudé
Anodisé ou vernissé à poudres en blanc ou noir
Diffuseur opal ou en microprisme
3000mm câble de suspension inclus, réglable sans outils


Dimmbare Versionen / dimmable versions
628-XXXXXXad = 1-10V dimm.
628-XXXXXXddd = DALI dimm.

W3 = LED 3000K
W4 = LED 4000K

UGR < 19

A++ - A

IP 20



LOG OUT 2 PD

220-240V AC/DC - CRI >80 - Binning SDCM 3

HIGH EFFICIENCY SYS 20W

mp: 3000K = 1860lm / 4000K = 1950lm
pm: 3000K = 1990lm / 4000K = 2090lm

628-42009X.. W3 L: 1134mm
628-42004X.. W4 L: 1134mm

HIGH EFFICIENCY SYS 25W

mp: 3000K = 2320lm / 4000K = 2440lm
pm: 3000K = 2490lm / 4000K = 2610lm

628-42509X.. W3 L: 1415mm
628-42504X.. W4 L: 1415mm

HIGH EFFICIENCY SYS 40W

mp: 3000K = 3720lm / 4000K = 3900lm
pm: 3000K = 3980lm / 4000K = 4180lm

628-44009X.. W3 L: 2259mm
628-44004X.. W4 L: 2259mm

HIGH EFFICIENCY SYS 50W

mp: 3000K = 4640lm / 4000K = 4880lm
pm: 3000K = 4980lm / 4000K = 5220lm

628-45009X.. W3 L: 2821mm
628-45004X.. W4 L: 2821mm

HIGH EFFICIENCY SYS 60W

mp: 3000K = 5580lm / 4000K = 5850lm
pm: 3000K = 5970lm / 4000K = 6270lm

628-46009X.. W3 L: 3383mm
628-46004X.. W4 L: 3383mm

HIGH EFFICIENCY SYS 75W

mp: 3000K = 6960lm / 4000K = 7320lm
pm: 3000K = 7470lm / 4000K = 7830lm

628-47509X.. W3 L: 4226mm
628-47504X.. W4 L: 4226mm

HIGH OUTPUT SYS 41W

mp: 3000K = 3440lm / 4000K = 3610lm
pm: 3000K = 3690lm / 4000K = 3860lm

628-42019X.. W3 L: 1134mm
628-42014X.. W4 L: 1134mm

HIGH OUTPUT SYS 51W

mp: 3000K = 4300lm / 4000K = 4510lm
pm: 3000K = 4610lm / 4000K = 4830lm

628-42519X.. W3 L: 1415mm
628-42514X.. W4 L: 1415mm

HIGH OUTPUT SYS 82W

mp: 3000K = 6880lm / 4000K = 7220lm
pm: 3000K = 7380lm / 4000K = 7720lm

628-44019X.. W3 L: 2259mm
628-44014X.. W4 L: 2259mm

HIGH OUTPUT SYS 102W

mp: 3000K = 8600lm / 4000K = 9020lm
pm: 3000K = 9220lm / 4000K = 9660lm

628-45019X.. W3 L: 2821mm
628-45014X.. W4 L: 2821mm

HIGH OUTPUT SYS 123W

mp: 3000K = 10320lm / 4000K = 10830lm
pm: 3000K = 11070lm / 4000K = 11580lm

628-46019X.. W3 L: 3383mm
628-46014X.. W4 L: 3383mm

HIGH OUTPUT SYS 153W

mp: 3000K = 12900lm / 4000K = 13530lm
pm: 3000K = 13830lm / 4000K = 14490lm

628-47519X.. W3 L: 4226mm
628-47514X.. W4 L: 4226mm





ZURÜCK ZUR ÜBERSICHT / BACK TO OVERVIEW



Project: CB Outlet | Lübeck | Germany

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

X = FARBE/COLOUR

- W white = 5
- S black = 6
- AE aluminium anodized = 8

.. = ABDECKUNG / COVER

-  microprismatic = mp
-  PMMA opal = pm