

Quadratische LED Halbeinbauleuchte
 Oberfläche Aluminium perlchrom lackiert
 Ein-, zwei- oder vierseitiger Lichtaustritt
 Zubehör separat ordern (S. 528)
 Geeignet für den Außenbereich (IP 54)

Square LED half-recessed luminaire
 Aluminium surface, pearl chrome painted
 1, 2 or 4 light points
 Order accessories separately (p. 528)
 Outdoor suitable (IP54)

Semincasso quadrato a LED
 In alluminio, verniciato in cromo satinato
 1, 2 o 4 punti luce
 Ordinare gli accessori separatamente (p. 528)
 Per esterni (IP54)

Demi-encastré carré à LED
 En aluminium vernissé en chrome satiné
 1, 2 ou 4 points d'émission
 Commander les accessoires séparément (p. 528)
 Pour extérieur (IP54)

W3 = LED 3000K

LED 2700K auf Anfrage / on request

A++ - **A**


IP54

Q1 WR

CRI>90
 exkl. LED Konverter (separat ordern)
 excl. LED converter (order separately)

SYS 2W · 500mA

56-5200ng2 42lm




Q2 WR

CRI>90
 exkl. LED Konverter (separat ordern)
 excl. LED converter (order separately)

SYS 2W · 500mA

56-5204ng2 52lm




Q4 WR

CRI>90
 exkl. LED Konverter (separat ordern)
 excl. LED converter (order separately)

SYS 2W · 500mA

56-5208ng2 70lm



LED CONVERTER Q1/Q2/Q4

75-mp15		4W	schaltbar / switchable	for 500mA	L 51 x B 32 x H 18mm
24-122428		6W	1 - 10V / PUSH Dimm.	for 500mA	L 67 x B 50 x H 22mm
24-122201		20W*	schaltbar / switchable	for 500mA	L 111 x B 52 x H 22mm
24-123400		20W*	1 - 10V / PUSH Dimm.	for 500mA	L 111 x B 52 x H 22mm
24-151403		20W*	DALI Dimm.	for 500mA	L 111 x B 52 x H 22mm

* nicht für den Einbau in Unterputzdose Ø68 geeignet
 * not suitable for mounting in housing Ø68

524 **Q1 / Q2 / Q4 WR**

Design: QZ Lighting



ZURÜCK ZUR ÜBERSICHT / BACK TO OVERVIEW

Project: Private residence | Austria

525