



LED Ringleuchte aus stranggepresstem Aluminium  
 Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet  
 LED Konverter im Leuchtenprofil integriert  
 Inkl. flache PMMA-Abdeckung

LED ring luminaire, extruded aluminium  
 Anodised surface, white or black powder-coated  
 Built-in LED converter in profile  
 Incl. flat PMMA diffuser

Lampada in alluminio estruso a forma di anello  
 Superficie anodizzata o verniciata a polvere in bianco o nero  
 Converter LED integrato nel profilo  
 Incl. copertura piatta in PMMA

Lampe en forme d'anneau en aluminium extrudé  
 Finition anodisée ou laquée blanc ou noir  
 Convertisseur intégré dans le profil  
 Incl. couvercle plat en PMMA

**W2** = LED 2700K  
**W3** = LED 3000K  
**W4** = LED 4000K



IP20

**RIDE RING PD**

220-240V AC/DC · CRI >90 · Binning SDCM 3 · DALI dimm.

SYS 38W / Ø 750mm	lm <b>W2</b>	lm <b>W3</b>	lm <b>W4</b>
<b>675-20101102WXXd</b>	3300	3590	3730
SYS 76W / Ø 1450mm	lm <b>W2</b>	lm <b>W3</b>	lm <b>W4</b>
<b>675-20201102WXXd</b>	6610	7180	7470

**ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE**

**W** = LICHTFARBE/LIGHT COLOUR

**XX** = FARBE/COLOUR

**W2** LED 2700K = 3  
**W3** LED 3000K = 9  
**W4** LED 4000K = 4

**W** white = 05  
**S** black = 06  
**AE** aluminium anodized = 08



ZURÜCK ZUR ÜBERSICHT / BACK TO OVERVIEW

Project: Bauwerk Parkett | Vienna | Austria